



Technical Datasheet

ESD Rubber Mats & Mat Kits RoHS Compliant 2059R Series

ESD Rubber Mats consist of a top layer static dissipative rubber laminated to a bottom layer of conductive rubber. The synthetic rubber work surface offers excellent resistance to oil, grease, and most common solvents. They are heat and solder resistant, will not delaminate, and are easy to clean.

APPLICATIONS: Computer Operators, Electronic Assembly, and Manufacturing, Pharmaceutical Plants, Cleanroom Operation, Fiber Optics, Aerospace, and Hospitals. To be used in work surface applications.

CONSTRUCTION

Static dissipative synthetic rubber laminated to a bottom layer of conductive rubber.

CHEMICAL RESISTANCE

They are resistant to degradation by inorganic acids, organic acids, reducing agents, detergent solutions, alcohols, aliphatic hydrocarbons, mineral oil, amines, and aldehydes.

TYPICAL PHYSICAL PROPERTIES ⁽¹⁾

COLOR	Blue
EMBOSS PATTERN	Matte finish, Non-Embossed
TEMPERATURE RESISTANCE	120 ^o F
GAUGE /THICKNESS	0.060" ± 10%; 1/16"
TENSILE	105 Kg/cm ²
ELONGATION	300%
DUROMETER	50 ± 5, Shore A
ESD PROPERTIES: R _{TT}	10 ³ - 10 ⁵
ESD PROPERTIES: R _{TG}	10 ⁷ - 10 ⁹
CHARGE DECAY TIME: 5KV TO 50V	<0.01 Seconds

⁽¹⁾ Specifications are subject to change at any time for a variety of reasons. If you have any questions, please call for the latest update.

Bertech® makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its this product for any particular purpose, nor does Bertech® assume any liability whatsoever arising out of the application or use of this product. It is ultimately the responsibility of the customer to determine a product's suitability for a particular application.