

# Copper Conductive Foil Tapes

## CFT Series

### RoHS & REACH Compliant

Copper Conductive Tapes, also known as EMI Shielding Tapes, are ideal for grounding flooring or building ground systems. They are made from a copper foil with an acrylic conductive adhesive. These conductive tapes are supplied on a paper liner for easy handling and cutting. Copper Conductive Tapes provide a very low rate of electrical resistance.


## Applications

- RFI/EMI shielding applications in the electrical and electronics industry
- Reliable point to point electrical contact
- Static charge draining

## Product Specifications <sup>(1)</sup>

Film Thickness	1.4 Mil	ASTM D-3652
Adhesive thickness	1.2 Mil	
Total Thickness	2.6 Mil	ASTM D-1000
Temperature Rating	266°F	
Tensile Strength	25 lbs./in.	ASTM D-3759
Adhesion to Steel	35 oz./in.	ASTM D-3330
Shielding Effectiveness	60 db – 80 db	
Color	Copper	
Liner	Paper	
Adhesion Type	Electrically Conductive	

(1) Specifications are subject to change at any time. If you have any questions, please contact us for the latest update.



Bertech® makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its this product for any particular purpose, nor does Bertech® assume any liability whatsoever arising out of the application or use of this product. It is ultimately the responsibility of the customer to determine a product's suitability for a particular application.



**Bertech**  
640 Maple Ave  
Torrance, CA 90503  
Phone: (310) 787-0337  
Email: [sales@bertech.com](mailto:sales@bertech.com)  
[www.bertech.com](http://www.bertech.com)

**PRODUCT DATA SHEET**