

Static Dissipative Finger Cots

ESDFC-B-5 Series

Static Dissipative Finger Cots, also known as Antistatic Finger Cots, are 4 mil thick. They are used with Class I Category A (<100V) static sensitive electronic devices and are powder free. Average surface resistivity is 10⁶ to 10⁸ ohms/square. They are packaged 720/bag.

Applications

- Computer Operators and Pharmaceutical Plants
- Electronic assembly and manufacturing
- Cleanroom operation and Fiber Optics
- Aerospace and Hospitals

Product Specifications ⁽¹⁾

Color	Black
Emboss Pattern	Smooth
Elongation	400%
Length	2.7"
Width	0.9" (S), 1.1" (M), 1.2" (L), 1.3" (XL)
Material	100 % Sheer Latex
Static Decay	5000 to 0 Volts in .01 seconds
Style	Rolled
Surface Resistivity	10 ⁶ to 10 ⁸ Ohms/Sq.
Thickness	4 Mil.
Type	Powder Free
Tensile Strength	16 Mpa

⁽¹⁾ Specifications are subject to change at any time. If you have any questions, please contact us for the latest update.



Bertech® makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its this product for any particular purpose, nor does Bertech® assume any liability whatsoever arising out of the application or use of this product. It is ultimately the responsibility of the customer to determine a product's suitability for a particular application.



Bertech
640 Maple Ave
Torrance, CA 90503
Phone: (310) 787-0337
Email: sales@bertech.com
www.bertech.com

PRODUCT DATA SHEET