

1 Mil Green Polyester Masking Tape

GPT1 Series

RoHS & REACH Compliant

Green Masking Tapes are made of 1 mil thick polyester film and 1.7 mil thick silicone adhesive with a primer in between. They are designed to masking during powder coating and splicing operations. They can be removed cleanly without leaving any residue. These tapes are packaged on a 3" core and are 72 yards long.


Applications

- Electronic Circuit Board Assembly
- Powder Coating of Switches and Control Panels
- Conformal Coating Process and Wave Soldering

Product Specifications ⁽¹⁾

Color	Green	
Adhesion Type	Silicone	
Film Thickness	1 Mil	ASTM D-3652
Adhesive Thickness	1.7 Mil	
Total Thickness	2.7 Mil	ASTM D-3652
Tensile Strength	25 lbs./in	ASTM D-3759
Elongation	100 %	ASTM D-3759
Dielectric Strength	4,200 volts	ASTM D-149
Operating Temperature	-73°C (-100°F) to 200°C (392°F)	
Length	72 Yards	
Adhesion to Steel	35 Oz./in	ASTM D-3330
Core	3 in. Plastic Core	

⁽¹⁾ Specifications are subject to change at any time. If you have any questions, please contact us for the latest update.



Bertech® makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its this product for any particular purpose, nor does Bertech® assume any liability whatsoever arising out of the application or use of this product. It is ultimately the responsibility of the customer to determine a product's suitability for a particular application.



Bertech
640 Maple Ave
Torrance, CA 90503
Phone: (310) 787-0337
Email: sales@bertech.com
www.bertech.com

PRODUCT DATA SHEET